



Features

- 1/4" SONY 410K/470K Pixels Ex-View HAD PS CCD
- 43x(f=3.2~138.5mm) Optical & 16x(0.1step) Digital Zoom
- High Resolution : 600 TV Lines
- Min. illumination :
- 0.0007 Lux (F1.2, 15 IRE, Sense-up x512, Color)
- 0.00007 Lux (F1.2, 15 IRE, Sense-up x512, B/W)
- 0~360° Endless Pan, 0~180° Tilting (D-Flip)
- Pan/Tilt Speed Min. 0.01°/sec, Max. 600°/sec
- Preset 512 ea, Auto Pan 4 ea, Pattern 3 ea
- Day Night Function (True), Sense-up Function (x512)
- Adaptive Digital Noise Reduction (3D + 2D)
- Back Light Compensation (Area Setting)
- Advanced Motion Detection Function
- eXtended Dynamic Range (XDR)
- Privacy Mask Function (12ea)
- DIS (Digital Image Stabilization)
- Time & Day Scheduling
- CCVC (Camera Control Via Coaxial, Controller : SCX-RD100)
- RS-485 (Half/Full)/RS-422 Control (Multi-Protocol support)
- Multi-Language OSD (E,F,G,S,I,J,R,P,C, etc) support
- Intelligent Video (Moved/Fixed/Fence/Tracking)
- Alarm Input 8 ea, Output 4 ea
- Operating Temp. : -10 ~ 50°